

Part Number TSGEC

Header TSGEC Heat Shrink End Caps

Description Thermosleeve-USA TSGEC Heat Shrink End Caps come with spiral adhesive coating that effectively protects cable endings against oxidation, ozone, and UV-radiation. Our TSGEC easily fits into the cable ending.


Minimum fully shrink temperature: 120°C.

Agency Approval & Compliance ROHS, and REACH compliant

Application TSGEC GEC is recommended for applications both in open air and underground power distribution cables with PVC, lead or XLPE sheaths.

Shrink Ratio and Operating Temperature TSGEC is available as a 2:1 material, shrinking to one half (50%) of its supplied size and ≤10% along the axis. The tubing's wall thickness also changes proportionally to the degree of recovery.

Thermosleeve-USA TSGEC Heat Shrink End Caps has a minimum shrink temperature of 120°C (248°F)

Standard Sizes and Dimensions


Part Number	As supplied (mm)		After recovered (mm)			
	L*(±10%)	D*(Min.)	A*(±10%)	d*(±10%)	l*(±10%)	Dw*(±10%)
TSGEC 105 12/4	40	12	15	4	40	2.6
TSGEC 110 14/5	45	14	18	5	42	2.2
TSGEC 115 20/6	55	20	25	6	55	2.5
TSGEC 120 25/8.5	68	25	30	8.5	65	2.5
TSGEC 130 35/16	90	35	35	16	83	3.3
TSGEC 135 40/16	83	40	35	16	75	3.3
TSGEC 140 55/26	103	55	50	26	105	3.5
TSGEC 150 75/36	120	75	55	36	115	4.2
TSGEC 160 100/52	140	100	70	52	130	5
TSGEC 170 120/60	150	120	70	60	150	5
TSGEC 180 145/60	150	145	70	60	150	5
TSGEC 190 160/82	150	160	70	80	133	4.5
TSGEC 200 200/90	170	200	70	90	145	4.5

D* = Inner diameter as supplied
 d* = Inner diameter after fully recovered

w* = Wall thickness after fully recovered
 A* = Length of adhesive
 L* = Length of end cap

Technical Properties

Test Items	Test Method	Test Requirement
Tensile strength	ASTMD2671	12MPa min
Ultimate Elongation	ASTMD2671	200% min
Volume Resistivity	IEC 93	1014Ω.cmmin.
Dielectric Strength	IEC 60243	12kN/mm (1.0mm)
Water Absorption	ISO 62	0.5% max.
Heat Shock @ 225°C/ 4Hrs	ASTMD2671	No cracking, dropping
Density	ASTMD792	1.0~1.1g/cm3
	Test Method	Typical Data

TSGEC tubing shall be homogeneous and essentially free from flaws, defects, pinholes, bubbles, seams, cracks and inclusions. Standard color is black.

Standard color: Black

Availability In standard lengths

Important Notice The information related to Thermosleeve-USA products in both printed or electronic format is believed to be reliable but the accuracy and completeness is not guaranteed. We suggest that before using this product, you evaluate and determine if it is suitable to your intended application. Thermosleeve-USA assumes no risk or liability associated with the use of this material. Any statements related to this product that are not contained in the current Thermosleeve-USA online or printed literature, or any contrary statements referenced on purchase order, shall have no force or effect unless expressly agreed to in writing and signed by an office of Thermosleeve-USA.

Limited Warranty/Limited Liability Thermosleeve-USA offers no guarantees in respect to the accuracy of the information detailed in this document and accepts no explicit or applied liability as to the products use. In no instance will Thermosleeve-USA be liable for any eventual, indirect or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product. Thermosleeve-USA specifications are subject to change without notice; including changes in materials and processing that do not affect compliance of the products specification. Thermosleeve-USA guarantees the product to be free from defects in material and manufacturing at the time of purchase. If this product is found to be defective within the warranty period, at our option we will refund the purchase price, replace or repair the Thermosleeve-USA product.